



Linea prodotti - Product line - Produktlinie - Ligne produits

Cella - Cold room - Kühlraum - Chambre froide

**UTA - AT** R 404 A / R 507

**+10 / +14°C**

Modello Model Modell Modele	Motore - Motor Motor - Moteur [kW]	Q R404A Evaporation temp. = 0 °C [kW]	Optional heating coil				Dati dimensionali - Dimensional data					Sound Level (see note) [dB(A)]	Refrigerant connections		Static useful prevalence [Pa]	Air volume [m3/h]
			Electric coil [kW]	Hot water coil			Dimensional daten - Dimensional données				IN		OUT			
				T <sub>IN</sub> water = 60°C [kW]	Pressure drop [kPa]	Water flow [dm3/h]	A [mm]	B [mm]	H [mm]	Weight [kg]						
<b>UTA 035 AT</b>	0,37	10,8	5	13,72	8	1.202	1.550	835	650	120	44	12	22	80	3.600	
<b>UTA 050 AT</b>	0,55	12,8	5	14,53	8	1.274	1.550	835	650	135	45	12	22	80	3.960	
<b>UTA 075 AT</b>	0,75	18,6	10	19,44	16	1.710	1.700	935	700	160	47	16	28	80	6.000	
<b>UTA 100 AT</b>	1,10	27,7	10	26,20	19	2.290	1.900	985	850	205	49	16	35	80	7.920	
<b>UTA 150 AT</b>	1,10	38,8	15	42,00	15	3.060	2.250	1.085	110	260	50	22	42	90	10.000	
<b>UTA 200 AT</b>	1,10	45,2	15	47,35	19	3.450	2.250	1.085	1.100	320	51	22	42	90	10.800	
<b>UTA 250 AT</b>	2,20	54,2	20	52,50	23	3.834	2.250	1.085	1.100	340	52	22	42	90	12.600	

Sound Level: livello di pressione sonora a 10 m – sound level at 10 m - Schalldruckpegel im Abstand von 10 m – niveau de pression sonore à 10 m



Linea prodotti - Product line - Produktlinie - Ligne produits

Cella - Cold room - Kühlraum - Chambre froide

**UTA - ATG** H<sub>2</sub>O + ethylene glycol 30%

**+10 / +14°C**

Modello Model Modell Modelle	Motore - Motor Motor - Moteur	Q Glycole T <sub>IN</sub> = -7 °C [kW]	Optional heating coil				P max without electric coil [kW]	I max [A]	P max with electric coil [kW]	I max [A]	Dati dimensionali - Dimensional data Dimensional daten - Dimensional données				Sound Level (see note) [dB(A)]	Refrigerant connections IN / OUT [inches]	Water-Glycol		Static useful prevalence [Pa]	Air volume [m <sup>3</sup> /h]
			Electric coil [kW]	Hot water coil							A [mm]	B [mm]	H [mm]	Weight [kg]			Pressure drop [kPa]	Flow [dm <sup>3</sup> /h]		
				T <sub>IN</sub> water = 60°C [kW]	Pressure drop [kPa]	Water flow [dm <sup>3</sup> /h]														
<b>UTA 035 AT</b>	0,37	10,7	5	13,72	8	1.202	0,37	1,2	5,37	8,4	1.550	835	650	120	44	1"	11	3.350	80	3.600
<b>UTA 050 AT</b>	0,55	12,8	5	14,53	8	1.274	0,55	1,7	5,55	8,9	1.550	835	650	135	45	1"	15	4.000	80	3.960
<b>UTA 075 AT</b>	0,75	18,6	10	19,44	16	1.710	0,75	2,2	10,75	16,6	1.700	935	700	160	47	1"	22	6.000	80	600
<b>UTA 100 AT</b>	1,10	27,0	10	26,20	19	2.290	1,10	2,8	11,10	17,2	1.900	985	850	205	49	1"	28	8.452	80	7.920
<b>UTA 150 AT</b>	1,10	38,0	15	42,00	15	3.060	1,10	2,8	11,10	24,5	2.250	1.085	110	260	50	1"	36	14.400	90	10.000
<b>UTA 200 AT</b>	1,10	45,0	15	47,35	19	3.450	1,10	2,8	11,10	24,5	2.250	1.085	1.100	320	51	1"	41	15.624	90	10.800
<b>UTA 250 AT</b>	2,20	54,0	20	52,50	23	3.834	2,20	5,3	22,20	34,2	2.250	1.085	1.100	340	52	1"	54	18.200	90	12.600

Sound Level: livello di pressione sonora a 10 m – sound level at 10 m - Schalldruckpegel im Abstand von 10 m – niveau de pression sonore à 10 m